

**Surface**

Material	Polyvinyl Chloride (PVC)
Thickness	220 $\mu$ $\pm$ 10%
Shrinkage margin	Approx. 0,2%
Fire reaction class	B-s1, d0
Certification	EN15102:2007 + A1 2011 / IMO MED
Durability (indoor)	10 years
Durability (outdoor)	N/A

**Adhesive**

Type	Permanent acrylic adhesive
Viscosity	3000–3500 cps (30°C)
Heat resistance	180°C
Adhesion after 20 min	1700 g/inch
Adhesion after 5 days	2700 g/inch
Color	Transparent

**Liner**

Material	Kraft paper
Thickness	120 $\mu$ $\pm$ 10%

**Application Instructions – Indoor**

Method	Dry application
Application temperature	10°C – 30°C
Applicable surfaces	Wood, plastic, metal, paper, glass, ceramic
Surface condition	Smooth, clean, free of residues
Surface type	Flat, vertical, slightly curved
Maximum stretch	Approx. 200% depending on model
PVC primer compatible	Yes
Cleaning	Non-abrasive damp cloth, neutral soap
Removal	Hot air and/or steam
Storage	5°C – 30°C, approx. 50% RH
Shelf life	24 months
Chemical resistance	Water, alcohol, beverages, neutral detergents

**Warranty**

Warranty period	5 years – indoor use
Coverage	Color change, yellowing, cracking, adhesion defects
Exclusions	Incorrect application or unsuitable surfaces

Last update: 30/06/2025 – Technical data subject to change without prior notice.